DISPENSING INTO DISPOSABLE DISPENSING DISH (BOTTLE)





Bottle cover "1" and "2" colors correspond to product bottle caps and labels. Please ensure bottle covers are applied correctly prior to use.

Consult Instructions for Use

Bottle covers help insulate G2-BOND Universal from excess heat and give greater control of dispensing drops to minimize wastage. Their use is highly recommended. Bottle covers may be reused with subsequent refills. Clean with water or wipe with alcohol. Do not sterilize. autoclave, or clean with chemical disinfectants.

ETCHING MODE SELECTION







Etch for 10-15 sec., rinse for 5 sec. and dry.

Light curing time

Light curing unit	Distance from light guide tip	
	<10mm	>10mm
Halogen / LED (700-1200 mW/cm²)	10 sec.	20 sec.
High power LED (more than 1200 mW/cm²)	5 sec.	10 sec.

BONDING PROCEDURE (INDICATIONS FOR USE [1])



Apply 1-PRIMER and wait 10 sec.



Dry.



Apply 2-BOND.



Make a uniform bond film.



Light cure.

INTRAORAL REPAIR (INDICATIONS FOR USE [3] [4])



Roughen surface. Rinse and dry.



Apply G-Multi PRIMER on ceramic surface.



Apply 1-PRIMER to all surface and wait 10 sec.



Dry.



Apply 2-BOND to all surface.



Make a uniform bond film.



Light cure.

SEALING OF TOOTH PREPARATION (INDICATIONS FOR USE [6])



Apply 1-PRIMER and wait 10 sec.



Dry.



Apply 2-BOND.



Make a uniform bond film.



Light cure.



Remove unpolymerized layer.